

MULTI-FREQUENCY, MULTI-GNSS ANTENNA



The A45 GNSS antenna is designed to support millimeter-level accuracy on land and marine applications. The A45 GNSS antenna offers support for present and future GNSS signals, including GPS, GLONASS, BeiDou, and Galileo. A45 is a multi-GNSS precision antenna and is ideal for various applications including surveys, RTK positioning and navigation, precise guidance, and machine control. Use the A45 antenna in challenging environments (such as near buildings and foliage) for superior multipath mitigation, stable phase center, and strong SNR's, even at low elevations. The ruggedized housing is made of an aluminum base that has been pretreated for the marine environment and will withstand salt, fog, and spray. The antenna easily passes the two-meter pole drop test.

GNSS Sensor

Signals Received: GPS L1/L2/L5, GLONASS G1/G2, BeiDou B1/B2/B3, SBAS, L-band, and Galileo E1/E5a and b

GNSS Frequency: 1.165 to 1.278 GHz
1.525 to 1.615 GHz

LNA Gain: 30 dBn
LNA Noise: 2.0 dB, typical

L-Band Sensor

L-Band Frequency: 1.525 - 1.585 GHz operation
L-Band LNA Gain: 30 dB

Power

Input Voltage: 3.3 to 15 VDC
Input Current: 25 mA, typical

Mechanical

Enclosure: Aluminum base with Lexan™ plastic cap
Dimensions: 4.7 H x 15.2 D (cm)

1.8 H x 6.0 D (in)
Weight: .50 kg (1.1 lbs)
Mount: 5/8 inch female thread
RF Connector: TNC (straight)

Environmental

Storage Temperature: -40° C to +85° C (-40°F to +185°F)

Operating Temperature: -40° C to +70° C (-40°F to +158°F)

Enclosure Rating: IP69K

Shock/Vibration: EP455

Phase Center Variation: Less than 2 mm at GPS L1, for elevations above 15 degrees

Hemisphere GNSS

8515 E. Anderson Drive
Scottsdale, AZ 85255, USA

Phone: +1 (480) 348-6380
Toll-Free: +1 (855) 203-1770
Fax: +1 (480) 270-5070

precision@hgns.com
www.hgns.com