



SWiFT CTDplus Turbidity

Multi-parameter Profiler

Designed from the outset with the intention of a seamless workflow, the SWiFT CTDplus Turbidity profiler provides survey-grade sensor technology coupled with the convenience of Bluetooth connectivity and rechargeable batteries. An integral GPS module, to geo-locate each profile, completes the package. Data can be easily and quickly downloaded and reviewed wirelessly, via Bluetooth, using Valeport's new Ocean software for Windows and Connect Pathway Edition for iOS and Android and instantly shared, in industry standard data formats through email and cloud services. A USB Cable and Bluetooth adapter are provided.

In addition to the directly measured Conductivity, Temperature and Depth measurements, Salinity, Density and Sound Velocity is calculated using the UNESCO international standard algorithm and Chen and Millero equation.

With an operational battery life of up to 5 days and the convenience of charging via USB, SWiFT CTDplus Turbidity is intended for offshore, coastal, harbour and inland environmental and hydrographic survey use to 500m and offers the highest quality CTD profiles in a compact, robust and portable package.

Valeport's Turbidity technology is essentially two sensors in one. The first is a "classic" nephelometer, using a 90° beam angle for turbidity levels between 0 and 2,000 NTU. The second sensor uses Optical Backscatter (OBS) for turbidity levels up to 10,000 NTU. The sensors output data separately and simultaneously at a programmable rate. This means that there is no need to switch ranges as conditions vary. Intelligent sampling and the use of a 24 bit ADC eliminates the need to switch gain.

Optionally, there is a deployment cage available to bolt onto the instrument to help get the SWiFT CTDplus Turbidity to depth in fast-flowing currents.

DATA SHEET

Product Details



MULTI-PARAMETER
CTD



SOUND
SPEED



OPTICAL



OCEAN & CONNECT
PATHWAY EDITION
SOFTWARE



Bluetooth



USB



Rechargeable
Battery



GPS

Valeport Limited

St. Peter's Quay, Totnes,
Devon TQ9 5EW United Kingdom

Telephone: +44 (0) 1803 869292

Email: sales@valeport.co.uk

www.valeport.co.uk



Sensor Specifications

The SWIFT CTDplus Turbidity is fitted with Valeport's conductivity sensor, temperature compensated piezo-resistive pressure transducer and a new fast response thermistor temperature sensor.

Turbidity

Linear Range	Nephelometer: 0 to >1,000 NTU - linear response ¹ OBS: 0 to >4,000 NTU - linear response ^{1&2} ¹ depending on suspended material ² >4,000 NTU has a non-linear monotonic response that allows derivation of higher values using look-up tables/secondary calibration
---------------------	---

Linearity	0.99 R ²
------------------	---------------------

Minimum Detection Level	0.03 NTU (Nephelometer)
--------------------------------	-------------------------

Conductivity

Range	0-80 mS/cm
--------------	------------

Resolution	0.001 m/s
-------------------	-----------

Accuracy	±0.01 m/s
-----------------	-----------

Temperature

Range	-5°C – +35°C
--------------	--------------

Resolution	0.001°C
-------------------	---------

Accuracy	±0.01°C
-----------------	---------

Pressure

Range	50 Bar
--------------	--------

Resolution	0.001% FS
-------------------	-----------

Accuracy	±0.01% FS
-----------------	-----------

Calculated Parameters and Accuracy

Calculations based on the UNESCO international standard algorithm and Chen and Millero equation

Sound Velocity	~0.25 m/s
-----------------------	-----------

Salinity	±0.01 PSU
-----------------	-----------

Density	±0.01 kg/m ³
----------------	-------------------------



Physical

Materials	Housing - Titanium Sensor Guard - Acetal Temperature Sensor - Titanium Pressure Sensor - Titanium Conductivity Sensor - Polyurethane coated titanium with ceramic core
------------------	--

Depth Rating	500m
---------------------	------

Dimensions	ø78mm x Length 350mm
-------------------	----------------------

Weight	2.7kg (in air) / 1.65kg (in water)
---------------	------------------------------------

Communications (set up and data offload)

USB Serial

Bluetooth v4 - low energy

Electrical

Battery	Internal rechargeable Li-ion battery pack
----------------	---

Battery life	5 days continuous operation
---------------------	-----------------------------

Charging	USB Typically, 1 hour fast charge will give 12 hours operation
-----------------	---

Software

iOS and Android Valeport Connect Pathway Edition for Bluetooth compatible mobile devices – instrument set up, data offload, display and translation to common data formats. Valeport's Ocean PC software, with both USB cable and Bluetooth connectivity, for instrument setup, data extraction, display and translation to common data formats.

Instrument and data time is synchronised to GPS, UTC.

Ordering

0660049-50-TU	SWIFT CTDplus Turbidity Profiler Titanium housing rated to 500m
----------------------	--

Supplied with	PC Bluetooth adapter USB interface and charging cable 1.5 A charger Valeport Ocean software Operating manual System transit case
----------------------	--



Datasheet Reference: SWIFT CTDplus Turbidity | May 2021

As part of our policy of continuing development, Valeport Ltd. reserve the right to alter at any time, without notice, all prices, specifications, designs and conditions of sale of all equipment - Valeport Ltd © 2021

